

高復元性スポンジパッキン

(商品コードSP)

圧縮永久歪の少ない高復元性のパッキンです。



RoHS

クリップで
応力をかける



応力を解放



用途

各種配電器函開口部のパッキンとしてご使用ください。

材質

EPDM製

	品番	厚さ (mm)	幅 (mm)	長さ・ロット	硬度 (°)	見掛比重	引張強さ (Mpa)	伸び (%)	50%圧縮永久歪	
									加熱 70°C×22h (%)	常温 22°C×22h (%)
通常タイプ	SHR-N-R0510	5	10	押出成形による 受注生産につき、 別途ご相談 ください	20	0.42	0.92	200	4.1	3.7
	SHR-N-R0515	5	15							
	SHR-N-R0520	5	20							
	SHR-N-R0808	8	8							
	SHR-N-R1010	10	10							
	SHR-N-R1015	10	15							
SHR-N-R1020	10	20								
ソフトタイプ	SHR-S-R0305	3	5		2	0.26	0.32	150	8.1	5.0
	SHR-S-R0310	3	10							
	SHR-S-R0315	3	15							
	SHR-S-R0320	3	20							
	SHR-S-R0505	5	5							
	SHR-S-R0510	5	10							
	SHR-S-R0515	5	15							
	SHR-S-R0520	5	20							
SHR-S-R1010	10	10								

【参考】一般的なEPスポンジ

※上記品番はテープ無です。テープ付の場合、品番末尾に「T」を付けてご注文ください。(例)SHR-N-R0510T


D

パッキン

異形ゴムパッキン


玉付き溝ゴム

色 : 黒
材質 : EPDM+SBR合成ゴム製



玉なし溝ゴム

色 : 黒
材質 : EPDM+SBR合成ゴム製



番号	A (mm)	B (mm)	C (mm)	D (mm)	定尺 (m)
NO.17	5	10	8	8.5	50
NO.20	3	10	6	8.5	50
NO.28	3	12	6	10.5	50
NO.31	5	10	7	9	50
NO.32	5	10.5	9	8.5	50
NO.34	3	17.5	7	15.5	50
NO.38	5	13	8	11.5	50
NO.45	5	15	8	13.5	50
NO.51	5	11	8	9.5	50
NO.54	3	10	9	7	50
NO.56	5	12	8	10.5	50
NO.57	5	15	8	13.5	50
NO.58	6	13	9	11.5	50
NO.62	7	22	12	19.5	50

番号	A (mm)	B (mm)	C (mm)	D (mm)	定尺 (m)
NO.95	5	19	8	17.5	50
NO.96	5	8.5	8	7	50
NO.97	4	12	13	7.5	50
NO.98	5	10	10	7.5	50
NO.100	2	11	5	9.5	50
NO.104	6	12.5	10	10.5	50
NO.105	12	11	16	9	50
NO.108	5	12	11	9	50
NO.112	3	14	6	12.5	50
NO.113	6	12.5	11	10	50
NO.114	3	12	6	10.5	50
NO.117	8	12	15	8.5	50
NO.120	12	14	16	12	50
NO.121	8	12.5	13	10	50
NO.122	7	12	12	9.5	50
NO.128	8	17	12	15	50
NO.130	6	14	14	10	50
NO.131	10	14	15	11.5	50
NO.135	9	16	13	14	50
NO.136	9	14	14	11.5	50
NO.140	10	13	13	11.5	50
NO.142	14	14	19	11.5	30
NO.147	17	15	23	12	25
NO.630	1	8	4	6.5	100