

型式 (SD-W寸法-L寸法-A許容電流)	端子幅W (mm)	標準長L (mm)	許容電流 (A)	公称断面積 (mm <sup>2</sup> )	標準寸法図
SD-25-200-200	25	200	200	38	
SD-25-200-300			300	76	
SD-25-200-380			380	114	
SD-25-200-450			450	152	
SD-40-300-290	40	300	290	50	
SD-40-300-410			410	100	
SD-40-300-520			520	150	
SD-40-300-580			580	200	
SD-40-300-690			690	250	
SD-40-300-770			770	300	
SD-50-330-450	50	330	450	100	
SD-50-330-650			650	200	
SD-50-330-820			820	300	
SD-50-330-970			970	400	
SD-50-330-1100			1,100	500	
SD-50-330-1220	1,220	600			
SD-75-350-680	75	350	680	150	
SD-75-350-760			760	200	
SD-75-350-860			860	250	
SD-75-350-940			940	300	
SD-75-350-1100			1,100	400	
SD-75-350-1240			1,240	500	
SD-75-350-1380			1,380	600	
SD-75-350-1630			1,630	800	
SD-75-350-1860			1,860	1,000	
SD-75-350-2070	2,070	1,200			
SD-100-400-860	100	400	860	200	
SD-100-400-970			970	250	
SD-100-400-1060			1,060	300	
SD-100-400-1240			1,240	400	
SD-100-400-1380			1,380	500	
SD-100-400-1530			1,530	600	
SD-100-400-1800			1,800	800	
SD-100-400-2000			2,000	1,000	
SD-100-400-2200			2,200	1,250	
SD-100-400-2500			2,500	1,500	
SD-150-( )-1460	150	500 or 560	1,460	400	
SD-150-( )-1640			1,640	500	
SD-150-( )-1800			1,800	600	
SD-150-( )-2100			2,100	800	
SD-150-( )-2350			2,350	1,000	
SD-150-( )-2600			2,600	1,200	
SD-150-( )-3000			3,000	1,600	
SD-150-( )-3400			3,400	2,000	
SD-150-( )-3800			3,800	2,400	
SD-150-( )-4100			4,100	2,800	
SD-200-( )-1850	200	550 or 610	1,850	500	
SD-200-( )-2360			2,360	800	
SD-200-( )-2640			2,640	1,000	
SD-200-( )-2900			2,900	1,200	
SD-200-( )-3260			3,260	1,500	
SD-200-( )-3800			3,800	2,000	
SD-200-( )-4200			4,200	2,500	
SD-200-( )-4700			4,700	3,000	
SD-200-( )-5100			5,100	3,500	

※全長寸法は標準寸法を示してあります。150幅、200幅に関しましては、型式( )内にL寸法をご指示ください。例)SD-150-500-1460、SD-200-610-1850